Heat Transfer — Japanese Research
Subject Index to Volume 25, 1996

Absorption chiller: **7**, 476-485
Absorption rate: **7**, 476-485
Adsorption: **7**, 420-433, 460-465, 466-475
Adsorption heat pump: **7**, 420-433, 460-465, 466-475
Adsorption performance: **7**, 420-433
Annulus flow: **2**, 103-119
Atmospheric pressure: **3**, 178-191
Axial flow: **2**, 103-119

Binary mixture: **6**, 342-361, 362-381
Boiling: **1**, 12-24; **5**, 293-307; **8**, 522-536
Boiling heat transfer: **1**, 51-63
Boundary layer: **2**, 88-102
Bubble growth: **1**, 51-63
Buoyant flow: **6**, 410-419

$Ca(OH)_2/H_2O/CaO$ series reaction: **6**, 400-409
Carbon-carbon composite: **5**, 308-322
Carbon dioxide: **4**, 214-224
Chart of interface: **8**, 499-510
Chemical reaction: **7**, 486-497
Cluster analysis: **8**, 511-521
Cold heat energy: **7**, 466-475
Combustion: **4**, 201-213
Condensation: **1**, 12-24, 25-38; **3**, 166-177; **4**, 214-224; **6**, 342-361, 362-381
Condensation coefficient: **3**, 166-177
Convective heat transfer: **1**, 1-11
Cooling experiment: **7**, 449-459
Cooling performance: **7**, 434-448
Copper cylinder: **3**, 178-191
Countercurrent flow: **1**, 25-38
Critical heat flux: **5**, 293-307; **8**, 522-536
Cylinder array: **6**, 410-419
Cylinder row: **3**, 192-200

Direct heat exchange: **7**, 420-433
Distillation: **3**, 135-150
Disturbance wave: **8**, 499-510, 511-521
Dropwise condensation: **6**, 342-361, 362-381
Drying: **3**, 151-165
Dynamic model: **3**, 151-165

Electromagnetic ultrasonic technique: **5**, 308-322
Electron collision: **7**, 486-497
Entrainment flow rate: **5**, 267-280, 281-292
Ethanol: **7**, 466-475
Evaporation: **1**, 12-24; **3**, 166-177
Excited state: **7**, 486-497
Experiment: **5**, 308-322; **6**, 342-361, 362-381; **8**, 537-553
Extended heat transfer surface: **6**, 382-399

Falling water limitation: **1**, 25-38
Flame spray: **4**, 201-213
Flow boiling: **3**, 178-191
Flow visualization: **1**, 39-50; **7**, 434-448
Fluidized-bed boiler: **2**, 120-134
Forced convection: **1**, 1-11; **2**, 65-75, 88-102, 103-119; **3**, 192-200; **6**, 382-399; **7**, 434-448, 449-459; **8**, 537-553, 554-567
Free convection: **4**, 214-224
Free stream turbulence: **2**, 65-75

Heat exchange: **7**, 460-465
Heat exchanger: **4**, 225-237
Heat of finite vaporization: **1**, 12-24
Heat of vaporization: **1**, 12-24
Heat release: **6**, 400-409
Heat sink: **7**, 434-448, 449-459; **8**, 537-553
Heat storage: **6**, 400-409
Heat transfer: **1**, 39-50; **2**, 65-75, 103-119; **3**, 151-165, 192-200; **4**, 214-224, 254-266; **6**, 342-361, 362-381, 410-419; **7**, 420-433, 434-448, 449-459, 460-465, 466-475; **8**, 537-553
Heat transfer coefficient: **2**, 120-134; **7**, 476-485
Heat transfer control: **1**, 1-11
Heat transfer enhancement: **1**, 1-11, 39-50; **2**, 88-102; **5**, 323-341; **6**, 382-399; **7**, 460-465; **8**, 554-567
Horizontal array: **6**, 410-419
Horizontal cylinder: **6**, 410-419
Huge wave: **8**, 499-510, 511-521
Hydrophobic membrane: **3**, 135-150

Heat Transfer — Japanese Research
Subject Index to Volume 25, 1996

Absorption chiller: **7**, 476-485
Absorption rate: **7**, 476-485
Adsorption: **7**, 420-433, 460-465, 466-475
Adsorption heat pump: **7**, 420-433, 460-465, 466-475
Adsorption performance: **7**, 420-433
Annulus flow: **2**, 103-119
Atmospheric pressure: **3**, 178-191
Axial flow: **2**, 103-119

Binary mixture: **6**, 342-361, 362-381
Boiling: **1**, 12-24; **5**, 293-307; **8**, 522-536
Boiling heat transfer: **1**, 51-63
Boundary layer: **2**, 88-102
Bubble growth: **1**, 51-63
Buoyant flow: **6**, 410-419

$Ca(OH)_2/H_2O/CaO$ series reaction: **6**, 400-409
Carbon-carbon composite: **5**, 308-322
Carbon dioxide: **4**, 214-224
Chart of interface: **8**, 499-510
Chemical reaction: **7**, 486-497
Cluster analysis: **8**, 511-521
Cold heat energy: **7**, 466-475
Combustion: **4**, 201-213
Condensation: **1**, 12-24, 25-38; **3**, 166-177; **4**, 214-224; **6**, 342-361, 362-381
Condensation coefficient: **3**, 166-177
Convective heat transfer: **1**, 1-11
Cooling experiment: **7**, 449-459
Cooling performance: **7**, 434-448
Copper cylinder: **3**, 178-191
Countercurrent flow: **1**, 25-38
Critical heat flux: **5**, 293-307; **8**, 522-536
Cylinder array: **6**, 410-419
Cylinder row: **3**, 192-200

Direct heat exchange: **7**, 420-433
Distillation: **3**, 135-150
Disturbance wave: **8**, 499-510, 511-521
Dropwise condensation: **6**, 342-361, 362-381
Drying: **3**, 151-165
Dynamic model: **3**, 151-165

Electromagnetic ultrasonic technique: **5**, 308-322
Electron collision: **7**, 486-497
Entrainment flow rate: **5**, 267-280, 281-292
Ethanol: **7**, 466-475
Evaporation: **1**, 12-24; **3**, 166-177
Excited state: **7**, 486-497
Experiment: **5**, 308-322; **6**, 342-361, 362-381; **8**, 537-553
Extended heat transfer surface: **6**, 382-399

Falling water limitation: **1**, 25-38
Flame spray: **4**, 201-213
Flow boiling: **3**, 178-191
Flow visualization: **1**, 39-50; **7**, 434-448
Fluidized-bed boiler: **2**, 120-134
Forced convection: **1**, 1-11; **2**, 65-75, 88-102, 103-119; **3**, 192-200; **6**, 382-399; **7**, 434-448, 449-459; **8**, 537-553, 554-567
Free convection: **4**, 214-224
Free stream turbulence: **2**, 65-75

Heat exchange: **7**, 460-465
Heat exchanger: **4**, 225-237
Heat of finite vaporization: **1**, 12-24
Heat of vaporization: **1**, 12-24
Heat release: **6**, 400-409
Heat sink: **7**, 434-448, 449-459; **8**, 537-553
Heat storage: **6**, 400-409
Heat transfer: **1**, 39-50; **2**, 65-75, 103-119; **3**, 151-165, 192-200; **4**, 214-224, 254-266; **6**, 342-361, 362-381, 410-419; **7**, 420-433, 434-448, 449-459, 460-465, 466-475; **8**, 537-553
Heat transfer coefficient: **2**, 120-134; **7**, 476-485
Heat transfer control: **1**, 1-11
Heat transfer enhancement: **1**, 1-11, 39-50; **2**, 88-102; **5**, 323-341; **6**, 382-399; **7**, 460-465; **8**, 554-567
Horizontal array: **6**, 410-419
Horizontal cylinder: **6**, 410-419
Huge wave: **8**, 499-510, 511-521
Hydrophobic membrane: **3**, 135-150

Immersed heat exchange surface: 2, 120-134
Impingement cooling: 7, 434-448, 449-459; 8, 537-553
Infrared image: 8, 554-567
Inner rotating cylinder: 2, 103-119
Interfacial profile: 8, 499-510, 568-579
Internal flow: 8, 554-567
Isobaric heat of vaporization: 1, 12-24
Isotherm: 8, 554-567
Isothermal heat of vaporization: 1, 12-24

Jet: 4, 201-213

K-mean algorithm: 8, 511-521

Labyrinth structure: 2, 103-119
Length scale of turbulence: 2, 65-75
Liquid drop: 2, 76-87
Liquid slug: 8, 511-521
Longitudinal fin: 8, 537-553
LSI plastic package: 6, 382-399
Lumped parameter system: 3, 151-165

Mach-Zehnder interferometer: 2, 88-102
Macrolayer thickness experiment: 8, 522-536
Mass transfer: 6, 342-361, 362-381
Mass transfer coefficient: 7, 476-485
Mathematical model: 4, 238-253
Maximum liquid holdup: 8, 511-521
Membrane separation: 3, 135-150
Mixture: 1, 12-24
Molecular orbital method: 7, 486-497
Multiphase flow: 1, 25-38; 5, 267-280, 281-292

Natural convection: 1, 39-50; 6, 410-419
Net vapor generation: 5, 293-307
Network analysis: 6, 382-399
Non-isothermal adsorption: 7, 466-475
Nonequilibrium: 7, 486-497
Nonuniform heating: 5, 293-307
Nuclear reactor: 1, 25-38
Numerical calculation: 3, 192-200

Ocean Thermal Energy Conversion (OTEC): 4, 225-237
Oscillating combustion: 5, 323-341
Oscillating plate: 8, 554-567
Oscillatory flow: 5, 323-341
Oxygen molecule: 7, 486-497

Packed bed drying: 4, 238-253
Phase-averaging measurement: 5, 323-341
Phase change: 2, 76-87
Phase transition: 3, 166-177
Pin-fin: 7, 434-448
Pipe flow: 5, 267-280, 281-292
Pipe flow pulsation: 5, 323-341
Plasma: 7, 486-497
Plug flow: 8, 568-579
Power storage: 6, 400-409
Prediction: 7, 434-448; 8, 537-553
Premature transition: 1, 51-63
Pressure drop: 7, 449-459; 8, 537-553
Pressure effect: 5, 267-280, 281-292
Pressure wave: 2, 76-87
Process system: 3, 151-165
Propagation: 2, 76-87
Pulsed combustion: 5, 323-341
Pulverized coal: 4, 238-253

Quantum mechanics: 7, 486-497
Quasi-steady state: 3, 178-191

Radial distribution of void fraction: 8, 568-579
Reflected shock wave: 3, 166-177
Rotating machine: 2, 103-119
Rotating Reynolds number: 2, 103-119

Semi-empirical correlation: 8, 522-536
Shape of gas slug: 8, 568-579
Shock tube: 3, 166-177
Silica gel: 7, 460-465
Silica gel model: 7, 420-433
Simultaneous measurement: 5, 308-322
Spherical powder: 4, 201-213
Static mixer: 4, 254-266
Subcooling: 3, 178-191
Subcooling effect: 1, 25-38
Subcritical region: 4, 214-224
Superactive carbon: 7, 466-475
Surface condition: 1, 51-63
Swirl: 5, 293-307
Swirl flow: 3, 178-191

Taylor number: 2, 103-119
Thermal diffusivity: 5, 308-322
Thermal engineering: 1, 51-63; 2, 76-87; 5, 267-280, 281-292
Thermal resistance: 6, 382-399; 7, 434-448, 449-459; 8, 537-553
Thermodynamic cycle: 4, 225-237
Thermodynamics: 1, 12-24
Thin longitudinal fin: 7, 449-459
Time-spatial behavior: 8, 499-510
Transient: 3, 178-191
Transient boiling: 1, 51-63

Transition: 4, 254-266; 7, 486-497
Tube bank: 7, 476-485
Tube bundle: 6, 342-361
Turbulent boundary layer: 2, 65-75
Turbulent film: 6, 342-361, 362-381
Turbulent flow: 4, 254-266
Turbulent promoter: 4, 254-266
Twisted tape: 3, 178-191
Type 304 stainless steel: 5, 308-322

Ultrasonic velocity: 5, 308-322

V-shaped promoter: 1, 39-50
Vapor explosion: 2, 76-87
Vaporization in continuous process: 1, 12-24
Vertical tube: 6, 362-381
Vertical upward flow: 5, 267-280, 281-292
Vortex shedding: 3, 192-200

Wake flow: 3, 192-200
Wake flow interaction: 3, 192-200
Wall jet: 1, 1-11
Wall material: 1, 51-63
Water recycling system: 3, 135-150
Wave velocity: 8, 511-521
Wave venation: 8, 499-510
Wave width: 8, 511-521
Wire-rim tire: 2, 120-134